



- 1-water draining gutter
- 2-polyurethane insulating wedge
- 3-Tile supporting profile
- 4-XDP FAKRO vapour permeable collar
- 17-rafter
- 22-thermal insulation
- 98-FX non-opening skylight FAKRO
- 150-EH-A FAKRO flashing lower element
- 151-top part of the flashing EH-A FAKRO
- 152-EH-A FAKRO flashing side element

**FIXED SKYLIGHT FX**

Frame width S[mm]	Frame height H[mm]	Nominal window WxK[mm]
623	699	563,6x673
	978	563,6x952
	1397	563,6x1371
826	978	766,6x952
	1178	766,6x1152
	1397	766,6x1371
1232	699	1172,6x673
	1178	1172,6x1152

	Vertical and horizontal cross-sections: FX non-opening Skylight with flashing EH-A for profiled roofing materials		<b>FORMAT</b> A4	<b>SCALE</b> 1:10/1:5

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality on the roof. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.